delta / delta plus

The universal film scanning systems.







Designed as an uncomplicated device for public or professional use, the *delta* microform scanner simply and efficiently digitizes all formats of microfilm as well as photographic materials.

Product advantages

- On-demand multiformat scanning roll film 16/35 mm, microfiche, jackets, aperture cards and photographic slides/negatives
- delta plus is now also available with color mode and high speed USB 3.0
- High-resolution area array with real-time on-screen view for highest productivity
- High-end customized lens for best microform clarity
- Follow-me-solutions
- Easy to use touch screen, film transport motorized and fully automatic with automatic image detection
- Direct output to searchable text (OCR)
- Whisper-quiet operation ideally for library applications

	delta	delta plus
Compatible film types	Microfiche; jackets; microcards; 16/35mm roll microfilm; cartridge (M-type, C-clip); aperture cards; photographic slides; negatives	
Image sensor	High-resolution area array with real-time on-screen view	
Lens Optics	Production-level, high-end customized lens developed specifically for microform clarity	
Capture mode	Grayscale or bi-tonal	Grayscale or bi-tonal, Color
Capture time	1/3 second per image (delta plus slightly faster)	
Reduction ratio	7x to 60x	7x to 96x
Maximum scan area	35 x 47 mm/ 1.38 x 1.85 inches (on film)	
Output resolution	100-600 dpi	
Output options	Scan to file, USB, print, email, cloud	Scan to CD/DVD, file, USB, print, email, cloud
Focus adjustment	Automatic and manual	
Sensor optimization	Included; fully adjustable optical image rotation	
Zoom adjustment	Motorized (optical) and digital	
File formats	TIFF (raw, compressed, multi-page); PDF (single, multi-page); JPEG; JPEG 2000; BMP	
Integrated USB output	Two built-in USB 2.0 ports*/flash-drive ports	
Scanner standards	Touch-screen; manual and moto- rized roll film pods, smart edit	Touch-screen; manual and motorized roll film pods, smart edit, opaque microcard LED, 3M adapter
Scanner options	RapidScan Batch Scanning; OCR and Annotation, Vendor interface kit, 3M adapter, Opaque microcard LED	Vendor interface kit; RapidScan Batch Scanning, OCR and Annotation
Light source	Custom-calibrated, color-compatible LED array	
Security	Integrated Kensington lock slot	
Interface	USB 2.0	USB 3.0
Operating system	Windows XP; Windows 7 (32-bit and 64-bit); Windows 8 (Metro Tile interface)	
Dimensions	50 x 290 x 200 mm/17.7 x 11.4 x 7.9 inches	
Weight	7.2 kg/16 lbs	

*backward compatibility

We reserve the right to make technical changes without notice.













Zeutschel GmbH \cdot Heerweg 2 \cdot 72070 Tübingen Tel.: +49 7071 9706-0 \cdot Fax: +49 7071 9706-44 info@zeutschel.com \cdot www.zeutschel.com